



SK600

STAND-ON SKID STEER



Ditch Witch®

SK600

Designed for landscape and irrigation jobs, the Ditch Witch® SK600 mini stand-on skid steer is maneuverable and easy to use, making it ideal for rental. Compact yet construction grade, the SK600 is built for heavy-duty operation, with a rugged design that improves machine longevity and ROI.



Compatible with an array of attachments for more versatility.

1

Advanced attachment latching system for more simple, secure connections.

2

Class-leading power to the attachment improves strength and performance.

3

24.8-hp (18.5 kW) Kubota® diesel engine delivers maximum power to the attachment for greater productivity.

4

Smaller, narrower frame is perfect for tough jobs in hard-to-reach areas.

10

600-lb (272-kg) rated operating capacity and a 76-inch (1.93-m) hinge-pin height for greater power.

11

Customer-driven control placement optimizes operator comfort and reduces fatigue.

5

Single-point, lockable fuel and hydraulic fluid tanks for improved security.

6

Two-way auxiliary control foot pedal to help maintain hydraulic for to the attachment.

7

Best-in-class operator platform design improves operator comfort and convenience for working on and off the machine.

8

Optimized hydraulics deliver a smoother ride for enhanced operator comfort and productivity.

9

SK600 ATTACHMENTS

The Ditch Witch® organization offers a full line of quick-change attachments compatible with the SK600 Mini Skid Steer. Visit the SK600 product page on ditchwitch.com to use our interactive attachment selector, or ask your Ditch Witch dealer about additional attachment options.

SK600 STAND-ON SKID STEER SPECIFICATIONS

DIMENSIONS (STD)

	U.S.	METRIC
Operating height, max std. bucket	103 in	2.63 m
Hinge pin height, max	76 in	1.93 m
Overall height of machine	54 in	1.39 m
Overall length of machine, std. bucket	105 in	2.68 m
Overall length of loader, no attachment	80 in	2.14 m
Wheelbase/track length	36 in	925 mm
Angle of departure	27°	
Machine width	33.5 in	850 mm
Ground clearance, min		
Center	8.5 in	216 mm
Side	4 in	101 mm

PERFORMANCE

Ground drive speed		
Forward/reverse	4.1 mph	6.6 km/h
Ground pressure		
7-in (180-mm) tracks	4.8 psi	0.33 bar
Tipping capacity	1,725 lb	782 kg
Operating capacity (35% of tipping capacity)	600 lb	272 kg
Machine weight (no attachment, fluids full)	2,418 lb	1096 kg

HYDRAULIC SYSTEM

Auxiliary circuit, double gear pump		
Flow rate	12 gpm	45.4 l/min
Pressure	3,000 psi	207 bar
Ground drive, dual hydrostatic pumps		
Flow rate	12.5 gpm	47.2 l/min
Pressure	3,625 psi	250 bar

POWER

	U.S.	METRIC
Engine	Kubota® D902-E4B	
Fuel	Diesel	
Number of cylinders	3	
Displacement	54.8 in ³	0.898 L
Bore	2.83 in	72 mm
Stroke	2.9 in	73.6 mm
Gross power rating (SAE J1995)	24.8 hp	18.5 kW
Rated speed	3,600 rpm	
Emissions compliance	EPA Tier 4	EU Stage IIIA

FLUID CAPACITIES

Hydraulic reservoir capacity	9.2 gal	35 L
Engine oil, w/filter	5 qt	4.7 L
Fuel tank capacity	10.5 gal	40 L

NOISE LEVEL

Operator ear sound pressure	90 dBA
Sound power	104 dBA

BATTERY

SAE reserve capacity rating	110 min
SAE cold crank @ 0°F (-18°C)	800 amps
Electrical system	12V

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

